



CARBON™ WALL MOUNT ENCLOSURE

CR9U61001

Wall mount enclosure safeguards 9U of 19" rack equipment

The CR9U61001 is designed for use in network closets, classrooms and other locations. This wall mount enclosure houses network switches and patch panels up to 22" deep. It includes convenient top panel cable access openings, perforated door and side panels for efficient airflow, adjustable rack angles, and square and threaded mounting holes. The CR9U61001 ships fully assembled for quick deployment, and can be customized with compatible accessories. It is covered by a 5-year limited warranty.



FEATURES

- Rack Type: Wall Mount Enclosure
- Height: 9U
- Stationary Capacity: 132 lbs
- Max. Mounting Depth: 22.2"
- Mounting Hole Types: Square and Threaded
- Warranty: 5 Years

TYPICAL APPLICATIONS

- Network Closets
- Retail Locations
- Back Office
- Classrooms

SPECIFICATIONS

| PHYSICAL | | PHYSICAL - CONT. | |
|-------------------------------|----------------------------------|---|-------|
| Rack Height | 9U | Weight Capacity - stationary load (lbs) | 132.3 |
| Color | Black RAL 9005 powder coat paint | Weight Capacity - stationary load (kg) | 60 |
| Door Type | Hex Perforated Metal Door | Factory Default Mounting Depth (in) | 17.2 |
| Rack Angle Mounting Hole Type | Square and #12-24 Mounting Hole | Factory Default Mounting Depth (mm) | 436 |

CARBON™ WALL MOUNT ENCLOSURE

CR9U61001



SPECIFICATIONS CONT.

PHYSICAL - CONT.

| | |
|--------------------------------------|-----------------------|
| Cable Access Opening Dimensions (in) | 9.8 x 2.2 |
| Cable Access Opening Dimensions (mm) | 250 x 56 |
| Max. Mounting Depth (in) | 22.2 |
| Max. Mounting Depth (mm) | 562 |
| Min. Mounting Depth (in) | 1.9 |
| Min. Mounting Depth (mm) | 47 |
| Dimensions (WxHxD in.) | 23.6 x 19.9 x 23.6 |
| Dimensions (WxHxD mm) | 600 x 505 x 600 |
| Net Weight (lbs) | 41.8 |
| Net Weight (kg) | 18.9 |
| Shipping Dimensions - WxHxD (in) | 26.18 x 22.44 x 26.18 |
| Shipping Dimensions - WxHxD (mm) | 665 x 570 x 665 |
| Shipping Weight (lbs) | 48.1 |
| Shipping Weight (kg) | 21.8 |

SPECIAL FEATURES

| | |
|--------------------------------|--|
| Numbered Rack Units | Yes |
| Rolling Casters | Optional |
| Removable Door and Side Panels | Yes |
| Reversible Front Door | Yes |
| Lockable Door and Side Panels | Yes, keyed alike |
| Ventilation | Perforated Door and Side Panels with Ventilated Top and Bottom |
| Cable Access | Top and Bottom Openings |
| PE Grounding Point | Yes |

ENVIRONMENTAL

| | |
|------------------|------|
| Protection Class | IP20 |
|------------------|------|

CERTIFICATIONS

| | |
|----------------|--|
| Certifications | CE, RoHS |
| Approvals | DIN41491, DIN41494, EIA/ECA-310-E, IEC 60297-3-100 |

WARRANTY

| | |
|------------------|-----------------|
| Product Warranty | 5 Years Limited |
|------------------|-----------------|